

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.



(54) Title  
**BURNER**

International Patent Classification(s)  
(51)<sup>5</sup> **F23D 014/24**

(21) Application No. : **29917/92** (22) Application Date : **04.12.92**

(30) Priority Data

(31) Number (32) Date (33) Country  
**1974/91 06.12.91 DK DENMARK**

(43) Publication Date : **10.06.93**

(71) Applicant(s)  
**HALDOR TOPSOE A/S**

(72) Inventor(s)  
**IVAR IVARSEN PRIMDAHL; THOMAS SANDAHL CHRISTENSEN; LISE OLSEN**

(74) Attorney or Agent  
**WATERMARK PATENT & TRADEMARK ATTORNEYS , Locked Bag 5, HAWTHORN VIC 3122**

(57)

Swirling-flow burner with improved design comprising U-shaped oxidizer and fuel gas injectors arranged coaxially at the burner face. The burner is further equipped with a bluff-body with static swirler blades extending inside the oxidizer injector.

AUSTRALIA  
Patents Act 1990

**PATENT REQUEST: STANDARD PATENT/PATENT OF ADDITION**

We, being the person identified below as the Applicant, request the grant of a patent to the person identified below as the Nominated Person, for an invention described in the accompanying standard complete specification.

Full application details follow.

[71] Applicant: HALDOR TOPSOE A/S  
Address: NYMOLLEVEJ 55, DK-2800 LYNGBY, DENMARK

[70] Nominated Person: HALDOR TOPSOE A/S  
Address: NYMOLLEVEJ 55, DK-2800 LYNGBY, DENMARK

[54] Invention Title: BURNER

[72] Name(s) of actual inventor(s): IVAR IVARSEN PRIMDAHL, THOMAS SANDAHL CHRISTENSEN AND LISE OLSEN

[74] Address for service in Australia: c/o WATERMARK PATENT & TRADEMARK ATTORNEYS, of The Atrium,  
290 Burwood Road, Hawthorn, Victoria 3122, Australia Attorney Code: WM

**BASIC CONVENTION APPLICATION(S) DETAILS**

[31] Application Number	[33] Country	Country Code	[32] Date of Application
1974/91	DENMARK	DK	6TH DECEMBER 1992

Drawing number recommended to accompany the abstract .....

By our Patent Attorneys,  
WATERMARK PATENT & TRADEMARK ATTORNEYS

.....  
Ian A. Scott  
Registered Patent Attorney

**DATED** this 3rd day of December 1992.

AUSTRALIA

---

*Patents Act 1990*

---

**ORIGINAL**  
**COMPLETE SPECIFICATION**  
**STANDARD PATENT**

Application Number:

Lodged:

Invention Title:           BURNER

The following statement is a full description of this invention, including the  
best method of performing it known to           :-US

This invention relates to a swirling-flow burner with separate fuel and oxidizer supply, for use in gas-fuelled combustion reactors.

5 Burners of this type are mainly used for firing gas-fuelled industrial furnaces and process heaters, which require a stable flame with high combustion intensities. Conventionally designed swirling-flow burners include a burner tube with a central tube for fuel supply surrounded by an oxidizer supply port. Intensive mixing of fuel and  
10 oxidizer in a combustion zone is achieved by passing the oxidizer through a swirler installed at the burner face on the central tube. The stream of oxidizer is, thereby, given a swirling-flow, which provides a high degree of internal and external recirculation of combustion products and thus  
15 a high combustion intensity.

As a general drawback of conventional swirling-flow burners of the above design, the burner face is at high gas flow velocities, as required for industrial burners of this design, exposed to overheating caused by the high degree of  
20 internal recirculation along the central axis of the combustion zone. Hot combustion products flow, thereby, back towards the burner face, which results in rapid heating up to high temperatures and, consequently, destruction of the face.

25 The general object of this invention is to eliminate this problem by an improved design of the burner face in the known swirling-flow burners.

This improved design is based on the observation that a stable flame with high combustion intensity and  
30 without detrimental internal recirculation of hot combustion products, is obtained when providing a swirling-flow of oxidizer with an overall flow direction concentrated along the axis of the combustion zone and at the same time directing the fuel gas flow towards the same  
35 axis.

In accordance with this observation, the swirling-flow burner of this invention comprises a burner tube and a central oxidizer supply tube concentric with and spaced from the burner tube, thereby defining an annular fuel gas channel between the tubes, the oxidizer supply tube and the fuel gas channel having separate inlet ends and separate outlet ends, wherein

5 a fuel gas injector is connected to the outlet end of the fuel gas channel, which fuel gas injector having a U-shaped cross sectional inner surface around a common axis of the burner tube and the injector;

10 an oxidizer injector is connected to the outlet end of the oxidizer supply tube, which oxidizer injector having a U-shaped cross sectional surface coaxially with and spaced from the fuel gas injector;

15 a fuel gas injection chamber is defined between the surfaces of the fuel gas and oxidizer injector;

an oxidizer injection chamber is defined within the surface of the oxidizer injector;

20 each of the injection chambers, having a U-shaped contour and being provided with a circular outlet end around the common axis;

a cylindrical bluff-body is coaxially arranged within the oxidizer injection chamber, the bluff-body having a domeshaped upstream end and a tapered downstream end; and

25 a swirler is installed on the bluff-body between its upstream end and its downstream end, the swirler having static swirler blades extending to the surface of the oxidizer injection chamber;

whereby, oxidizer supplied to the oxidizer injection chamber is injected into a downstream combustion zone in a swirling-flow by combined action of the bluff-body and the swirler, which oxidizer flow is directed around a  
5 common axis of the injection chambers and the combustion zone after having passed through the oxidizer injection chamber;

the oxidizer is mixed in the combustion zone with fuel gas being supplied to the fuel gas injection chamber and injected into the combustion zone in an inwardly flow  
10 direction towards the axis of the combustion zone after having passed through the fuel gas injection chamber.

The swirling-flow induced in the swirler promotes mixing of fuel gas and oxidizer by increasing the area of  
15 their contact. Effective mixing is obtained, when adjusting the pitch angle of the swirler blades to an angle of between 15° and 75°, preferably between 20° and 45°.

At the same time, the inwardly directed flow pattern along the axis of the combustion zone caused by the  
20 U-shaped contours of the injection chamber prevents recirculation of hot combustion products in the high temperature region around the axis of the combustion zone, which otherwise would lead to overheating of the burner face.

Furthermore, the inwardly directed flow pattern leads to a high degree of external recirculation in the low  
25 temperature outer region of the combustion zone. From this region only cooled combustion products flow back to the burner face, where the products are being sucked into the hot combustion zone area and reheated there.  
30

During use of the burner according to the invention in gas fired reactors, the recycle stream of cooled combustion products protects advantageously the reactor walls surrounding the combustion zone against impingement of hot  
35 combustion products and prolongs the lifetime of the reactor.

The temperature at the burner face close to the outlet end of the injection chambers may further be lowered by forming the oxidizer injector at the outlet end of the oxidizer injection chamber sharp-edged with a minimum tip  
5 angle. Reduced heating and suitable mechanical strength of the injector are obtained at tip angles of between 15° and 60°, preferably between 15° and 40°.

As a further advantage of the burner according to the invention, the high degree of external recirculation of  
10 cooled combustion products provides a homogeneous temperature distribution in the combustion outlet zone.

This is of great importance during operation of fired catalytic reactors, where the product yield highly depends on the temperature distribution in the catalyst  
15 bed, which typically is arranged in the combustion outlet zone.

Accordingly, the burner of this invention is particularly useful in heating and carrying out catalytic processes in gas-fuelled reactors.

20 The above objects and advantages of the invention are more fully described in the following description by reference to the drawing, in which the sole Figure shows schematically a sectional view of a swirling-flow burner according to a specific embodiment of the invention.

25 In the Figure, a burner tube 2 surrounds coaxially to common axis 16 a central oxidizer supply tube 4, defining a fuel gas supply channel 6 between the tubes.

An injector 10 with a U-shaped cross sectional inner surface around axis 16 is installed at outlet end 8  
30 of burner tube 2. Injector 10 accommodates a coaxial injector 12 with a U-shaped cross sectional surface mounted on the outlet end 14 of central tube 4.



The U-shaped injector form may conveniently be obtained by machining a suitable metallic body having a cylindrical part and a conical part. The transition angle between the cylindrical and conical part is thereby preferably in the range of  $115^\circ$  and  $170^\circ$ .

The surfaces of injectors 10 and 12 enclose a fuel gas injection chamber 18 communicating with the fuel gas supply channel 6, and within injector 12 an oxidizer injection chamber 20, to the outlet end of central tube 4.

Injection chambers 18 and 20 have U-shaped contours around axis 16, with circular outlet ends 22 and 24 coaxially arranged to axis 16. Outlet end 24 of injection chamber 20 may open into the lower part of injection chamber 18.

The edge of injector 12 surrounding the outlet end of the oxidizer injection chamber is tapered with a minimum tip angle  $\gamma$  in order to protect the edge against overheating as described more detailed below.

Injection chamber 20 is further equipped with a cylindrical bluff-body 26 coaxially spaced to the inner surface of chamber 20. Bluff-body 26 is provided with domeshaped upstream end 28 and tapered downstream end 30. Around the cylindrical surface of bluff-body 26 a swirler 32 is installed with static swirler blades (not shown) extending to the surface of injection chamber 20.

In operating the burner with the above design, fuel gas is supplied through channel 6 to injection chamber 18 and injected into a combustion zone downstream to outlet end 24 of injection chamber 20. By means of the U-shaped contour of injection chamber 18 the injected stream of fuel gas is in the combustion zone directed towards the common axis 16 of injection chamber 18 and the combustion zone as indicated by arrows in the Figure. In the combustion zone the fuel gas stream is mixed with oxidizer supplied in central tube 4 and injected into the combustion zone through injection chamber 20.

Before being injected into the combustion zone the oxidizer stream is brought into swirling-flow by passage through swirler 32. Furthermore, by means of bluff-body 26 and the U-shaped contour of injection chamber 20, the swirling oxidizer stream is discharged into the combustion zone in an overall flow directed around the axis of the combustion zone.

As a result, mixing of the oxidizer and fuel gas stream is mainly accomplished in the high temperature region around the axis of combustion zone. Thereby, deleterious internal recirculation of hot combustion products within this region is prevented. Recirculation is only established in the low temperature outer region of the combustion zone, resulting in reduced material temperatures close to the outlet ends of the injection chambers. As mentioned hereinbefore, the temperature in this region may further be controlled by angle  $\gamma$  of the oxidizer injector edge around the outlet end of the oxidizer injection chamber, whereby the mixing zone of oxidizer and fuel gas is kept at an increasing distance from the edge at decreasing tip angles.

Having thus described the invention with reference to a specific embodiment thereof, changes and alternations, which will readily be apparent to those skilled in the art, are contemplated as within the scope of the invention. For example, in applications requiring very high combustion intensities the burner face may further be protected against high temperatures by addition of an inert gas or steam in the region of the outlet ends of injection chambers 18 and 20 introduced at the edge of injector 12 through a bored channel within oxidizer injector 12.

**CLAIMS**

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. Swirling-flow burner comprising a burner tube and a central oxidizer supply tube concentric with and spaced from the burner tube, defining an annular fuel gas channel between the tubes, the oxidizer supply tube and the fuel gas channel having separate inlet ends and separate outlet ends, wherein

a fuel gas injector is connected to the outlet end of the fuel gas channel, which fuel gas injector having a U-shaped cross sectional inner surface around a common axis of the burner tube and the injector;

an oxidizer injector is connected to the outlet end of the oxidizer supply tube, which oxidizer injector having a U-shaped cross sectional surface coaxially with and spaced from the fuel gas injector;

a fuel gas injection chamber is defined between the surfaces of the fuel gas and oxidizer injector;

an oxidizer injection chamber is defined within the surface of the oxidizer injector;

each of the injection chambers, having a U-shaped contour and being provided with a circular outlet end around the common axis;

a cylindrical bluff-body is coaxially arranged within the oxidizer injection chamber, the bluff-body having a domeshaped upstream end and a tapered downstream end; and

a swirler is installed on the bluff-body between its upstream end and its downstream end, the swirler having static swirler blades extending to the surface of the oxidizer injection chamber;

whereby, oxidizer supplied to the oxidizer injection chamber is injected into a downstream combustion zone in a swirling-flow by means of the bluff-body and the swirler, which oxidizer flow is directed around a common  
5 axis of the injection chambers and the combustion zone after having passed through the oxidizer injection chamber;

the oxidizer is mixed in the combustion zone with fuel gas being supplied to the fuel gas injection chamber and injected into the combustion zone in an inwardly flow  
10 direction towards the axis of the combustion zone after having passed through the fuel gas injection chamber.

2. The swirling-flow burner of claim 1, wherein the swirler blades are arranged in the swirler with a pitch angle of  $15^{\circ}$ - $75^{\circ}$ , preferably of  $20^{\circ}$ - $45^{\circ}$ .

15 3. The swirling-flow burner of claim 1, wherein the injectors have a tip angle of  $15^{\circ}$ - $60^{\circ}$ , preferably  $15^{\circ}$ - $40^{\circ}$  at the outlet ends of the injection chambers.

4. The use of a burner according to anyone of the preceding claims, for carrying out catalytic processes in a  
20 gas fuelled reactor.

DATED this 3rd day of December 1992.

HALDOR TOPP /S

WATERMARK PATENT & TRADEMARK ATTORNEYS  
"THE ATRIUM"  
290 BURWOOD ROAD  
HAWTHORN. VIC. 3122.

**ABSTRACT**

Swirling-flow burner with improved design comprising U-shaped oxidizer and fuel gas injectors arranged coaxially at the burner face. The burner is further equipped with a bluff-body with static swirler blades extending inside the oxidizer injector.

